

MODEL: CAN-340

340 Pints/Day Submittal Sheet



SPECIFICATIONS

Capacity (80F @ 60% RH)	340 PPD
ENERGY FACTOR	5.92 pints per kw
VOLTAGE	208 - 240V/60Hz / 1Ph
CURRENT (POWER)	10 Amps
AIRFLOW	1100 CFM (1868 M3/H)
POWER CORD TYPE	SJTW 14 AWG, 3M
BREAKER SIZE	25 Amps
WEIGHT	212 lbs 96.2 kg
DIMENSIONS	33L x 26.4W x 24H inches 83.82L x 67.056W x 60.96H cm
OPERATING RANGE	16°-32°C 20% RH - 90% RH
BTU HEAT OUTPUT	6100 BTU
PLUG TYPE	NEMA L6-20P

FEATURES

CONTROL	DIGITAL ONBOARD OR EXTERNAL 3RD PARTY
FILTER SIZE	508 x 508 x 50mm 20 x 20 x 2 inches
REFRIDGERANT	R32 (1.7 kg)
DRAIN CONNECTION	¾ NPT (P-TRAP REQUIRED)
COIL TYPE	COPPER TUBE, ALUMINUM EPOXY
CONDENSATE PAN	Stainless Steel 304
WARRANTY	5-YEARS LIMITED, 1 YEAR ALL INCLUSIVE
CERTIFICATION TYPE	ETL G

MODEL: CAN-340

340 Pints/Day Submittal Sheet

